



(19)

(11) Publication number: **08169779 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **06332338**(51) Intl. Cl.: **C04B 38/00 C04B 28/02 E21D 11/00**(22) Application date: **14.12.94**

(30) Priority:

(43) Date of application
publication: **02.07.96**(84) Designated contracting
states:(71) Applicant: **CHICHIBU ONODA CEMENT
CORP**(72) Inventor: **SHIRASAKA MASARU
MORISHITA NOBUAKI
NOGUCHI MASAOKI**

(74) Representative:

**(54) FOAMED MORTAR
CAVITY FILLER**

(57) Abstract:

PURPOSE: To obtain an foamed mortar cavity filler not deteriorating foamability even in the case of use of an ordinary foaming agent, preventing the separation of materials without using a thickener and having satisfactory characteristics while using fly ash in combination with cement as a hardening material.

CONSTITUTION: Water is added to a mixed hardening material obtd. by mixing fly ash with cement in a weight ratio of 4:6 to 2:8 to prepare a slurry contg. 50-70wt.% water. This slurry is mixed and blended with a proper amt. of a foaming agent.

COPYRIGHT: (C)1996,JPO**BEST AVAILABLE COPY**

THOMSON
DELPHION

RESEARCH

PRODUCTS

INSIDE DELPHION

[Home](#) | [About Us](#) | [Products](#)
[Search: Quick/Number](#) | [Boolean](#) | [Advanced](#) | [Derwent](#)
[Help](#)

The Delphion Integrated View

 Get Now: ☒ PDF | [More choices...](#)

 Tools: Add to Work File: ☐ Create new Work File ☒ 

 View: INPADOC | Jump to: ☒ Go to: [Derwent](#)
☒ [Email this to a friend](#)

Title: JP8169779A2: FOAMED MORTAR CAVITY FILLER

Derwent Title: Foamed mortar cavity filler - prepd. from slurry of fly ash and cement, and mixed with blowing agent [\[Derwent Record\]](#)

Country: JP Japan

Kind: A

Inventor: SHIRASAKA MASARU;
MORISHITA NOBUAKI;
NOGUCHI MASAOKI;

Assignee: CHICHIBU ONODA CEMENT CORP
[News, Profiles, Stocks and More about this company](#)

Published / Filed: 1996-07-02 / 1994-12-14

Application Number: JP1994000332338

IPC Code: [C04B 38/00](#); [C04B 28/02](#); [E21D 11/00](#); [C04B 28/02](#); [C04B 103/42](#);
[C04B 111/40](#); [C04B 111/70](#);

Priority Number: 1994-12-14 JP1994000332338


Abstract: PURPOSE: To obtain an foamed mortar cavity filler not deteriorating foamability even in the case of use of an ordinary foaming agent, preventing the separation of materials without using a thickener and having satisfactory characteristics while using fly ash in combination with cement as a hardening material.

CONSTITUTION: Water is added to a mixed hardening material obtd. by mixing fly ash with cement in a weight ratio of 4:6 to 2:8 to prepare a slurry contg. 50-70wt.% water. This slurry is mixed and blended with a proper amt. of a foaming agent.

COPYRIGHT: (C)1996,JPO

Family: None

Other Abstract Info: CHEMABS 125(16)203134U CAN125(16)203134U DERABS C96-358434
DERC96-358434



[View Image](#)

1 page



[Nominate](#)



[this for the Gallery...](#)